ED HIGHBAY



Xtreme LED are bring its new 4th Generation LED Highbay to the Australian market with 190lm/w light efficency.

- ✓ Lumileds Chip
- ✓ Optional Sensor
- ✓ Die-Cast Aluminum Heat Sink

5 YEAR

WARRANTY

- ✓ Anti-glare lens
- ✓ Rated >54,000hrs



MARKET LEADING PERFORMANCE

| SPECIFICATIONS | H76W-S | H90W-S | H120W-S | H150W-S | H170W |
|---------------------------------------|-----------------------------|---------------|---------------|---------------|----------------|
| Wattage | 76W | 90W | 120W | 150W | 170W |
| Lumen Output | 14400 LM | 17100 LM | 22800 LM | 28500 LM | 32300 LM |
| Light Efficiency | 190LM/W | 190LM/W | 190LM/W | 190LM/W | 190LM/W |
| Optional Accesory | Daylight / Occupancy Sensor | Motion Sensor | Motion Sensor | Motion Sensor | Without Sensor |
| Dimensions | 310x191mm | 310x191mm | 370x185mm | 370x185mm | 370x196mm |
| Packaging | 382x382x196mm | 382x382x196mm | 382x382x196mm | 442x442x206mm | 442x442x206mm |
| LED Brand | Lumileds | | | | |
| LED Type | L128-2780RB35000G1 | | | | |
| Driver Type | Integrated Driver | | | | |
| Diffuser Type | PC Lens | | | | |
| Dimming | 0-10V dimming standard | | | | |
| IP Level | IP65 | | | | |
| Color Temperature | 5000K | | | | |
| Beam Angle | 90° | | | | |
| Input Voltage | 200-240V~ | | | | |
| CRI | >80 | | | | |
| Housing | Die-cast aluminium | | | | |
| Housing Color | Black | | | | |
| Storage Temperature | -40 °C TO 80 °C | | | | |
| Warranty | 5 year product warranty | | | | |
| · · · · · · · · · · · · · · · · · · · | | | | | |